



HOT WATER WEED REMOVAL SYSTEM

GREEN JET 1010

PRESSURE

8
bar

FLOW RATE

600
l/h

ABSORBED POWER

0,8
kW

EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORK



MUNICIPALITIES



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



MODULAR
BUILD-UP



IPC'S
EXCLUSIVE
BOILER


SPECS



STANDARD LIFTING HOOK TO
BE RAISED AND TRANSPORTED
ANYWHERE



DIRECT WATER SUPPLY OR
SUCTION WITH EXTERNAL
TANK



CONTROL PANEL SHOWING:
ON/OFF SWITCH, NETWORK
INDICATOR LIGHT, FLAME
CONTROL LIGHT, WARMING
LACK OF ANTISCALE, SERVICE
WARNING LIGHT (150 HRS),
READY WARNING LIGHT
(TEMPERATURE REACHED)

TECHNICAL DATA

GREEN JET 1010 M

Code		GNVA40051
Operating pressure	bar/Mpa	8/0,8
Flow rate	l/h	600
Outlet water temperature max	°C	~100
Power supply	Ph-V-Hz/A	1-230-50/3,8
Absorbed power	kW	0,8
Motor power	kW	0,55
Remote control		DTS
Pump(type)	IPC volumetric rotary vane pump is self-priming, high-performance. The pump body is brass made	
Boiler thermal power	kW	74
Fuel consumption	Kg/h	5,2
Fuel tank	l	18
Antiscale tank	l	2
Dimension (LxWxH)	cm	83x109x100
Weight	Kg	142

STANDARD EQUIPMENT

CODE: IPPR40027
HANDGRIP ML330 +
EXTENSION 350 mm



CODE: LCLC40025
70 cm LANCE WITH SPRAY
BAR (SPRAY BAR L= 50 cm)



CODE: TBAP39122
H.P. HOSE 20 m
(NO-MARKING)



OPTIONAL

CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg

