



HIGH-PRESSURE WASHERS - HOT WATER

TWOCK-H

PRESSURE

130÷200
bar

FLOW RATE

1800÷2500
l/h

ABSORBED POWER

11÷12,8
kW



EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



IPC'S
EXCLUSIVE
BOILER

SPECS



FLEXIBLE COUPLING
BETWEEN MOTOR AND PUMP



CONTROL PANEL PROVIDED
WITH EMERGENCY
SHUTDOWN



PLUNGER PUMP WITH SIX
CERAMIC PISTONS AND TWO
BRASS HEADS

TECHNICAL DATA

		TWOCK-H D1341PIT	TWOCK-H D2030PIT
Code		IDAC49714	IDAC49713
PERFORMANCE			
Operating pressure	bar/Mpa	30-130/3-13	30-200/3-20
Flow rate	l/h	2500	1800
Outlet water temperature	°C	30-150	30-150
Power supply	Ph-V-Hz/A	3-400-50/24,9	3-400-50/24
Absorbed power	kW	11	12,8
Motor pole/rpm		4-1400	6-1000
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/ 2 brass/ceramic	IPC plunger/ 2 brass/ceramic
Boiler thermal power	kW	81	81
Fuel consumption	kg/h	8,4 x 2	8,4 x 2
Fuel tank	l	54	54
Detergent tank	l	-	-
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	140x86x86	140x86x86
Weight	kg	448	480

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN02317
H.P. NOZZLE 1/4 2515
(FOR 1341)



CODE: UGLN02312
H.P. NOZZLE 1/4 2509
(FOR 2030)



CODE: TBAP40011
HIGH PRESSURE HOSE
15 m



OPTIONAL ACCESSORIES

CODE: LCPR29363
STEAM LANCE - P70



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: LCPR40089
EXTENSION P70 TURBO
D.1.0 (FOR 2030)



CODE: KTRI28935
LANCE HOLDER



CODE: KTRI28914
ROTATING ARM



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: AVTB39119
INOX HOSE REEL KIT

