

### ONE STEP AHEAD

**ADDRESSING NEW CLEANING CHALLENGES** 

Cleaning is consistently evolving, as we seek to meet higher hygiene standards ever more effectively.

IPC is closely connected to the latest and best practises of cleaning and is committed to deliver new solutions that boost cleaning efficiency, addressing those areas and tasks that are evolving fastest.

We have thus developed a complete range of new solutions, responding to the latest precautionary practises focused to protect communities all around the world.



















**NEW TOUCHLESS DISPENSER** 

### TOUCHLESS DISPENSER STATION







**CHEMICAL DISPENSER STATIONS** 

**NEW DISPOSABLE MOPS AND WIPE** 

### EFFCIENT DISPOSABLE











### **MOPPING WIPES:**

Disposable Microfiber Mop 42 x 14 cm. 100% Polyester

60% Polyester 40 % Viscose

### **MULTI PURPOSE WIPE:**

Disposable Multipurpose Wipe 30 x 30 cm. 40% Polyester 60% Cellulose.

## HYGENETROLLEYS









**NEW STEAM GENERATOR** 

### INCOMPARABLE STEAM

Unique steam temperature stability combined with special accessories designed to maximize cleaning performances.

Designed for very narrow spaces and aisle ways.

**OPERATING PRESSURE: 4,5-7 BAR (MODEL S 5014 T)** 

**OPERATING STEAM TEMPERATURE: 160° C** 

FLOW RATE: 0-140 G/MIN (MODEL S 5014 T)







**NEW WORKING STATION SOLUTION: STEAM GENERATOR AND TROLLEY** 

### MULTIPURPOSE in STEAM TROLLEYS

Integrated working stations to optimize cleaning efficiencies.

Modular trolleys combined with SG-50 or SG-10 steam generators.





**TROLLEY SG-50** 

**TROLLEY SG-10** 

SG-50 WITH INTEGRATED TROLLEY **NEW HIGH PRESSURE WASHER** 

# OUTLET WATER TEMPERATURE 100°C

Unique water temperature stability both for high and low pressure modes

PRESSURE: 30-200 BAR

FLOW RATE: 900 L/H

OUTLET WATER TEMPERATURE: 100° C
AT MAX FLOW/PRESSURE WITH 12°C WATER INLET TEMPERATURE





### SPRAYING SYSTEM

- Built in and portable plug in system.
- Easily retrofittable on scrubber-driers.
- Highly reliable piston pump with brass fittings

**TANK CAPACITY: 15 L** 

**BATTERY TYPE: LI-ION BATTERY 12 V - 8 AH** (3,5 H RUNNING TIME)

### **SPRAYER SPECS ON SCRUBBER:**

- Spraying path: 850/1200 mm
- Full tank productivity: from 2500 to 3000 sqm/h
- Full tank run time: approx. 45 min
- Automatic spray stop-start: upon scrubber movement

**MODULAR SPRAYING SYSTEM** 

# 4-11



Spraying lance from operator position



Trolley Spray




Backpack Spray

**NEW VACUUM CLEANERS** 

GP 1/27 EXT SPRAY
GP 2/62 EXT SPRAY

### ALL IN ONE VACUUM TO SPRAY

- Vacuum-spray, double function machine.
- Injection/extraction functions included.
- HEPA Dual Filtration System









- ULPA filtration with aerosol cartridge leak test.
- H Certification according IEC 60335-260 AA.

### **UPSTREAM TESTED FILTERING MATERIAL:**


ULPA U15 99.9995% MPPS EFFICIENCY

### **DOWNSTREAM TESTED FILTERING MATERIAL:**

HEPA H14 99,995% MPPS EFFICIENCY

MEDICAL COMPLIANCE TO IEC 60601-1

ISO 5 PHARMACEUTICAL COMPLIANCE TO ISO 14644-1







GS 1/33 H ISO5 ULPA









