



PURE WATER CLEANING SYSTEM

GTE GREEN TUBE



PRESSURE

~8 bar

FLOW RATE

~3 l/min

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP

TECHNICAL DATA

		GTE
Code		APTA40009
PERFORMANCE		
Operating pressure	bar	~8
Pure water flow	l/min	~3
Water in/out connections	gas	3/4" only out connection
Maximum working height	m	~15
Productivity	m ² /h	up to 100
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	0,3
Dimension (LxWxH)	cm	33x41x145
Weight	kg	26

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/TENSILE STRUCTURES

STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS MEMBRANE



CODE: PRCH40034
POWDER FOR OSMOTIC MEMBRANE FILTER MAINTENANCE



CODE: KTRI40147
FILTER KIT: - 1 pcs sediment filter - 1 pcs active carbon filter - 1 pcs deionizing resin cartridge



CODE: TBBP40079
DRAINAGE TUBE



CODE: TBFX40008
15 m FLEXIBLE HOSE WITH FITTINGS



CODE: CNPR40007
GASKET LUBRICANT



CODE: AZMC40006
HAND-HELD TDS METER

