

GTO GREEN TUBE

PRESSURE

FLOW RATE

System pressure

Water Supply



EXCLUSIVE CHARACTERISTICS

POWER FILTER

- ERGONOMICS
- DURABILITY

TECHNICAL DATA

IECHNICAL DAIA		GTO
Code PERFORMANCE		APTA40008
Operating pressure	bar	Supply pressure (minimum 3bar)
Pure water flow	l/min	Water supply
Water in/out connections	gas	3/4'
Maximum working height	m	~10
Productivity	m²/h	up to 80
Power supply		-
Absorbed power	kW	-
Dimension (LxWxH)	cm	33x28x145
Weight	kg	15

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/ TENSILE STRUCTURES



CODE: FTAC40002 REVERSE OSMOSIS MEMBRANE



CODE: PRCH40034 POWDER FOR OSMOTIC MEMBRANE FILTER MAINTENANCE CODE: KTRI40147 FILTER KIT: - 1 pcs sediment filter - 1 pcs active carbon filter - 1 pcs deionizing resin cartridge



CODE: TBBP40079 DRAINAGE TUBE



CODE: TBFX40008 15 m FLEXIBLE HOSE WITH FITTINGS



CODE: CNPR40007 GASKET LUBRICANT



CODE: AZMC40006 HAND-HELD TDS METER

