







Code

PLANET 22S ATEX

CE EX II 3D Ex tc IIIB T200°C Dc IP6X

Available 60Hz version

EXCLUSIVE FEATURES

- M & H FILTER CLASSIFICATION
- TOTAL FILTRATION
- H CERTIFICATIONESD COMPLIANCE
- MULTI STAGE FILTRATION
- DOUBLE STAGE MOTORS AND TURBINE
- **BIG AND BRAKED WHEELS**
- NEW CONCEPT PROTECTIONS FOR INTERNAL ZONE 20
- EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22

- CONDUCTIVE WHEELS WITH BRAKES
- STATIC DISSIPATING FILTERS
- **CONDUCTIVE POLY LINER BAGS WITH SAFETY STRING**
- ▶ PCB PREFILTER & ADDITIONAL CARTRIDGE
- COMPLIANCE WITH CLASS H CERTIFICATION
- HEPA H13 CARTRIDGE AND FILTERS SURFACE AREA
- ► FILTER OVERPRESSURE INDICATORS
- **▶** SAFETY DISPOSAL SYSTEMS
- RESISTANT FRAMEWORK AND INLET PLUG FOR SAFE TRANSFER
- **▶** GROUNDING SYSTEM

PLANET 22S ATEX

ASID00566

TECHNICAL DATA		
Usage		DRY
Motor		1
Power	W	1000-1200 max
Voltage	V	220-240
Water lift	mmH₂0	2470
Airflow	m³/h	210
Tank Capacity/Material	l	30/steel 430
Cable length	m	10
Sound Pressure Level	dB(A)	72
Diameter of inlet	mm	60
Diameter of accessories	mm	38/32
Dimensions (LxWxH)	mm	500x500x980
Weight	Kg	30 Available 60Hz vers

STANDARD EQUIPMENT

CODE: FTDP00618
CONDUCTIVE
MAIN FILTER





















OPTIONAL ACCESSORIES

Conductive tool kit Ø38/32 mm	PMDT00015
High Reach Cleaning ATEX	AVAILABLE
Anti-Static tool kit Ø38-60 mm	PMDT00326